


DMA63Nplus RESIDUAL CURRENT BREAKERS WITH OVERCURRENT PROTECTION

PEP ecopassport®

Product Environmental Profile



Registration number:	ABBG-00608-V01.02-EN	Drafting rules:	PCR-ed4-EN-2021 09 06
Contact information:	EPD_ELSB@abb.com	Supplemented by:	PSR-0005-ed3-EN-2023 06 06
Verifier accreditation number:	VH50	Information and reference documents:	www.pep-ecopassport.org
Date of issue:	June-24	Validity period:	5 years
Independent verification of the declaration and data in compliance with ISO 14025: 2006			
Internal:	☐	External:	☒
The PCR review was conducted by a panel of experts chaired by Julie Orgelet (Ddomain)			
PEPs are compliant with XP C08-100-1:2016 and EN 50693:2019 or NF E38-500 :2022 The components of the present PEP may not be compared with components from any other program.			
Document complies with ISO 14025:2006 "Environmental labels and declarations. Type III environmental declarations"			





Purpose & Embedding Sustainability

Committed to continually promoting and embedding sustainability across operations and value chain, aspiring to become a role model for others to follow. Focusing with this Purpose on reducing harmful emissions, preserving natural resources championing ethical and humane behaviour.




General information

Reference product	2CSR256154R1165 - AEG DMA63NPLUS B16 A30
Description of the product	The AEG DMA63NPLUS products are universal Residual Current Circuit Breaker with Overcurrent Protection; the devices are designed for the protection of end user single-phase circuits against overload and short-circuit currents; it also provides protection against the effects of sinusoidal alternating earth fault currents and against indirect contacts and additional protection against direct contacts.
Functional unit	The functional unit is designed to protect the installation against overloads and short circuits and protect people and premises at risk of fire or explosion against insulation defects in a circuit with rated voltage 415V rated current 16A, with 3P+N poles, a rated breaking capacity 6kA, the tripping curve type B, the sensitivity 30mA, and the differential protection type A, according to the appropriate use scenario, and in the Household/Commercial and during the reference service life of the product of 20 years.
Other products covered	AEG DMA63NPLUS homogeneous family Ue [V] 415 In [A] 10/13/16/20/25/32 Np 3P+N Icn [A] 6 kA Tripping curve Cd B C,
Manufacturing address	Viale dell'Industria, 18 20009 Vittuone (MI) - Italy www.aeg-low-voltage.com



Constituent Materials



■ Plastics 179,89 g ■ Metals 273,64 g ■ Others 53,77 g

Total weight of reference product and packaging

507,3

g

Plastics as % of weight		Metals as % of weight		Others as % of weight	
Name and CAS number	Weight%	Name and CAS number	Weight%	Name and CAS number	Weight%
PA	23,0	Steel	42,0	Cardboard	6,8
Glass Fiber	8,7	Copper	9,2	wood	2,5
PC	2,1	Other Metal	1,9	Paper	0,8
PTFE / PPS / PE	1,6	Aluminium	0,9	Miscellaneous	0,5

Total weight of the reference product 456,9 g plus packaging 50,4g



Additional Information

Manufacturing	The manufacturing stage includes the production and transportation to the manufacturer's last logistic platform of DMA63Nplus and its packaging. The production occurs at the factory located in Santa Palomba (RM).
Distribution	The transport from the factory to Vignate, Milan was taken into account. For the distribution of the product from Vignate to the final customer, the intracontinental transport scenario provided by PCR-ed4-EN-2021 09 06 standard was adopted, considering the European macro-area.
Installation	The installation phase only implies manual activities and no energy is consumed. This phase also includes the disposal of the packaging of the product. Statistical average data from Eurostat databases [2023] were considered for the disposal of the product and its packaging.
Use	DS203NC dissipate some electricity due to power losses. The average power loss of the switch has been calculated as follow: - Nominal current load rate as 15% (Household / Commercial); - RSL of 20 years; - Functioning time of 30% of the RSL (α). No maintenance is planned for the product.
End of life	The default end of life scenario provided by the IEC/TR 62635 [2019] document has been adopted, considering the product transport by lorry over 1000 km and its disposal.
Benefits and loads beyond the system boundaries	The potential benefits derives from the impacts prevented by recycling and waste to energy recovery of the packaging in the installation phase




Environmental Impacts

Reference lifetime	20 years
Product category	Residual Current Circuit Breaker with Overcurrent Protection
Installation elements	No installation materials are required in the life cycle of the product.
Use scenario	The calculation of the use stage electricity consumption from the average power consider the following assumptions: - Nominal current load rate as 15% (Household / Commercial); - RSL of 20 years; - Functioning time of 30% of the RSL. No maintenance is planned for the product
Geographical representativeness	Europe
Technological representativeness	Technological representativeness refers to the specific production process for primary data.
Software and database used	SimaPro 9.4.0.2 and ecoinvent 3.9.1

Energy model used

Manufacturing	ABB GO energy mix 2022. The energy-related processes used for the remaining inputs are those included in the ecoinvent v3.9.1 datasets.
Installation	No energy consumption occur during the installation stage.
Use	Electricity, low voltage {RER} market group for electricity, low voltage Cut-off, S
End of life	The energy-related processes used for the inputs of the end-of-life stage are those included in the ecoinvent datasets selected for the analysis.

Common base of mandatory indicators



Environmental impact indicators

Indicator		Unit	Total	Manufacturin g	Distribu tion	Installation	Use	End of life	Benefits
GWP	Total	kg CO2 eq.	1.05E+01	5,44E+00	3,90E-01	4,00E-02	4,34E+00	3,38E-01	-1,13E+00
	Fossil	kg CO2 eq.	1.02E+01	5,31E+00	3,89E-01	4,22E-03	4,18E+00	2,79E-01	-1,16E+00
	Biogenic	kg CO2 eq.	3.69E-01	1,28E-01	3,54E-04	3,57E-02	1,46E-01	5,95E-02	3,57E-02
	Luluc	kg CO2 eq.	1.63E-02	5,47E-03	1,90E-04	1,61E-06	1,04E-02	2,45E-04	-9,87E-04
ODP		kg CFC-11 eq.	2,08E-05	2,07E-05	8,52E-09	7,17E-11	7,98E-08	4,12E-09	-9,00E-09
AP		H+ eq.	1,01E-01	7,24E-02	1,61E-03	1,85E-05	2,40E-02	2,98E-03	-2,24E-02
EP	Freshwater	kg P eq.	9,29E-03	5,12E-03	2,74E-05	4,70E-07	3,96E-03	1,77E-04	-1,76E-03
	Marine	kg N eq.	1,29E-02	7,71E-03	6,15E-04	1,55E-05	3,88E-03	7,10E-04	-1,80E-03
	Terrestrial	mol N eq.	1,38E-01	9,19E-02	6,56E-03	7,49E-05	3,51E-02	3,85E-03	-2,21E-02
POPCD		kg NMVOC eq.	3,87E-02	2,38E-02	2,36E-03	2,78E-05	1,13E-02	1,30E-03	-7,34E-03
ADP	Minerals & metals	kg SB eq.	8,34E-04	7,54E-04	1,26E-06	1,35E-08	5,07E-05	2,77E-05	-2,39E-04
	Fossil	MJ	1,68E+02	6,40E+01	5,55E+00	4,31E-02	9,52E+01	3,44E+00	-1,27E+01
WDP		m³ eq. depr.	4,02E+00	2,83E+00	2,25E-02	2,83E-04	1,07E+00	9,70E-02	-3,72E-01

Resource use indicators

Indicator	Unit	Total	Manufacturin g	Distribution	Installation	Use	End of life	Benefits
PERE	MJ	3,05E+01	8,72E+00	8,62E-02	1,67E-03	2,13E+01	3,74E-01	-1,05E+00
PERM	MJ	9,86E-01	9,86E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERT	MJ	3,15E+01	9,71E+00	8,62E-02	1,67E-03	2,13E+01	3,74E-01	-1,05E+00
PENRE	MJ	1,62E+02	5,79E+01	5,55E+00	4,31E-02	9,52E+01	3,44E+00	-1,27E+01
PENRM	MJ	6,11E+00	6,11E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRT	MJ	1,68E+02	6,40E+01	5,55E+00	4,31E-02	9,52E+01	3,44E+00	-1,27E+01

Common base of mandatory indicators

Use of secondary materials, water, and energy resources

Indicator	Unit	Total	Manufacturing	Distribution	Installation	Use	End of life	Benefits
SM	kg	3.39E-02	3,39E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0.00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0.00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW	m³	1.60E-01	7,92E-02	7,91E-04	1,64E-05	7,71E-02	3,15E-03	-9,77E-03

Waste category indicators

Indicator	Unit	Total	Manufacturing	Distribution	Installation	Use	End of life	Benefits
HWD	kg	9.04E-04	6,75E-04	3,53E-05	2,55E-07	1,67E-04	2,60E-05	2,60E-05
N-HWD	kg	2.09E+00	1,07E+00	2,71E-01	9,93E-03	3,83E-01	3,57E-01	-1,99E-01
RWD	kg	8.00E-04	1,01E-04	1,80E-06	4,10E-08	6,87E-04	1,03E-05	-5,78E-08

Output flow indicators

Indicator	Unit	Total	Manufacturing	Distribution	Installation	Use	End of life	Benefits
CfRu	kg	0.00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MfR	kg	5.37E-01	2,48E-01	0,00E+00	3,44E-02	0,00E+00	2,55E-01	0,00E+00
MfER	kg	0.00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
EE	MJ	1.47E-01	0,00E+00	0,00E+00	4,05E-02	0,00E+00	1,07E-01	0,00E+00

Other indicators

Indicator		Unit	Total
Biogenic Carbon	Product	kg of C	8.21E-04
	Packaging	kg of C	3.00E-02

Optional indicators

Indicator	Unit	Total	Manufacturing	Distribution	Installation	Use	End of life	Benefits
Tot PE	MJ	2.00E+02	7,37E+01	5,64E+00	4,47E-02	1,17E+02	3,81E+00	-1,37E+01
Efp	Dise inc	5.25E-07	3,81E-07	3,19E-08	3,32E-10	8,80E-08	2,34E-08	-1,01E-07
IrHH	kBq U-235 eq	3.13E+00	3,95E-01	7,43E-03	1,64E-04	2,68E+00	4,02E-02	-3,80E-04
ETX FW	CTUe	1.08E+02	8,61E+01	2,74E+00	4,46E-02	1,60E+01	3,58E+00	-2,45E+01
HTX CE	CTUh	2.83E-08	1,99E-08	1,78E-10	4,57E-12	1,97E-09	6,24E-09	-1,21E-09
HTX N-CE	CTUh	8.33E-07	7,02E-07	3,91E-09	4,92E-11	7,84E-08	4,87E-08	-2,38E-07
IrLS	Pt	6.31E+01	3,90E+01	3,31E+00	2,30E-02	1,86E+01	2,24E+00	-6,55E+00

Extrapolation Factors

For other products than the Reference product covered by this PEP, the environmental impacts for each phase of the lifecycle are obtained by a linear correlation with respect to weight for the production, distribution, and end-of-life phase and with respect to average power loss for the use phase. Each environmental indicator value shall be calculated using the following formulas:

For the manufacturing stage, distribution stage and end-of-life stage: $y = ax_1 + b$ where x_1 is the weight of the product

For the use stage: $y = ax_2 + b$ where x_2 is the average power loss of the product

* if the coefficient is !1, the impacts of the phase of the life cycle are assimilated to the Reference product, meaning that the impacts are unchanged in comparison to the Reference product

Impact Category	Manufacturing		Distribution		Installation		Use		End of Life	
	a1	b1	a2	b2	a2	b2	a4	b4	a5	b5
GWP-total	1.16E-02	2.45E-01	7.83E-04	3.89E-02	0.00E+00	4.00E-02	1.93E+01	3.70E-03	1.12E-03	3.80E-04
GWP-fossil	1.14E-02	1.93E-01	7.82E-04	3.89E-02	0.00E+00	4.22E-03	1.86E+01	3.57E-03	8.86E-04	3.01E-04
GWP-biogenic	1.70E-04	5.13E-02	7.12E-07	3.54E-05	0.00E+00	3.57E-02	6.48E-01	1.25E-04	2.34E-04	7.93E-05
GWP-luluc	9.44E-06	1.24E-03	3.82E-07	1.90E-05	0.00E+00	1.61E-06	4.63E-02	8.91E-06	9.80E-07	3.32E-07
ODP	4.61E-08	2.27E-08	1.71E-11	8.52E-10	0.00E+00	7.17E-11	3.54E-07	6.81E-11	2.17E-11	7.35E-12
AP	1.56E-04	2.38E-03	3.24E-06	1.61E-04	0.00E+00	1.85E-05	1.07E-01	2.05E-05	7.92E-06	2.69E-06
EP-freshwater	1.12E-05	1.22E-04	5.51E-08	2.74E-06	0.00E+00	4.70E-07	1.76E-02	3.38E-06	5.39E-07	1.83E-07
EP-marine	1.62E-05	4.44E-04	1.23E-06	6.14E-05	0.00E+00	1.55E-05	1.72E-02	3.31E-06	1.25E-06	4.22E-07
EP-terrestrial	1.96E-04	4.31E-03	1.32E-05	6.56E-04	0.00E+00	7.49E-05	1.56E-01	3.00E-05	1.13E-05	3.85E-06
POCP	5.03E-05	1.26E-03	4.74E-06	2.36E-04	0.00E+00	2.78E-05	5.01E-02	9.62E-06	3.92E-06	1.33E-06
ADPE	1.64E-06	1.87E-05	2.53E-09	1.26E-07	0.00E+00	1.35E-08	2.25E-04	4.33E-08	6.39E-08	2.17E-08
ADPF	1.37E-01	2.72E+00	1.12E-02	5.55E-01	0.00E+00	4.31E-02	4.23E+02	8.12E-02	1.30E-02	4.43E-03
WDP	6.08E-03	1.03E-01	4.53E-05	2.25E-03	0.00E+00	2.83E-04	4.74E+00	9.11E-04	2.80E-04	9.50E-05
CRU	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR	4.34E-04	5.32E-02	0.00E+00	0.00E+00	0.00E+00	3.44E-02	0.00E+00	0.00E+00	9.18E-04	3.11E-04
MER	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EE	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.05E-02	0.00E+00	0.00E+00	5.97E-05	2.03E-05
PM	8.14E-10	1.62E-08	6.41E-11	3.19E-09	0.00E+00	3.32E-10	3.91E-07	7.51E-11	6.62E-11	2.25E-11
IRP	8.42E-04	1.79E-02	1.49E-05	7.43E-04	0.00E+00	1.64E-04	1.19E+01	2.29E-03	1.72E-04	5.83E-05
PENRE	1.23E-01	2.59E+00	1.12E-02	5.55E-01	0.00E+00	4.31E-02	4.22E+02	8.12E-02	1.30E-02	4.43E-03
PENRM	1.33E-02	1.32E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	1.37E-01	2.72E+00	1.12E-02	5.55E-01	0.00E+00	4.31E-02	4.22E+02	8.12E-02	1.30E-02	4.43E-03
PERE	1.36E-02	2.62E+00	1.73E-04	8.61E-03	0.00E+00	1.67E-03	9.47E+01	1.82E-02	1.52E-03	5.16E-04
PERM	5.90E-05	9.59E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	1.37E-02	3.58E+00	1.73E-04	8.61E-03	0.00E+00	1.67E-03	9.47E+01	1.82E-02	1.52E-03	5.16E-04
PE	1.50E-01	6.30E+00	1.13E-02	5.64E-01	0.00E+00	4.47E-02	0.00E+00	0.00E+00	1.46E-02	4.94E-03
SM	7.71E-09	3.39E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	9.18E-04	3.11E-04	0.00E+00	0.00E+00
RSF	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	5.97E-05	2.03E-05	0.00E+00	0.00E+00
FW	1.62E-04	6.64E-03	1.59E-06	7.91E-05	0.00E+00	1.64E-05	3.42E-01	6.57E-05	1.00E-05	3.39E-06
HWD	1.46E-06	2.28E-05	7.10E-08	3.53E-06	0.00E+00	2.55E-07	7.42E-04	1.43E-07	7.30E-08	2.48E-08
NHWD	2.27E-03	4.97E-02	5.45E-04	2.71E-02	0.00E+00	9.93E-03	1.70E+00	3.26E-04	5.93E-04	2.01E-04
RWD	2.15E-07	4.57E-06	3.62E-09	1.80E-07	0.00E+00	4.10E-08	3.05E-03	5.86E-07	4.40E-08	1.49E-08
ETP-fw	1.87E-01	2.11E+00	5.50E-03	2.74E-01	0.00E+00	4.46E-02	7.10E+01	1.36E-02	9.29E-03	3.15E-03
HTP-c	4.29E-11	7.14E-10	3.57E-13	1.78E-11	0.00E+00	4.57E-12	8.73E-09	1.68E-12	1.42E-11	4.81E-12
HTP-nc	1.51E-09	2.42E-08	7.86E-12	3.91E-10	0.00E+00	4.92E-11	3.48E-07	6.68E-11	1.13E-10	3.83E-11
SQP	6.00E-02	1.21E+01	6.64E-03	3.31E-01	0.00E+00	2.30E-02	8.24E+01	1.58E-02	7.00E-03	2.37E-03
BCProd	1.75E-06	3.47E-05	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCPack	0.00E+00	3.00E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Extrapolation Factors

Product Code	Product Name	Weight [g]	Average Power loss [W] @0,15In
2CSR256154R1105	DMA63NpB10/030	460	0,126
2CSR256154R1165	DMA63NpB16/030	448	0,225
2CSR256154R1205	DMA63NpB20/030	448	0,266
2CSR256154R1255	DMA63NpB25/030	471	0,232
2CSR256154R1325	DMA63NpB32/030	471	0,340
2CSR256154R1104	DMA63NpC10/030	460	0,126
2CSR256154R1164	DMA63NpC16/030	448	0,225
2CSR256154R1204	DMA63NpC20/030	448	0,266
2CSR256154R1254	DMA63NpC25/030	471	0,232
2CSR256154R1324	DMA63NpC32/030	471	0,340
2CSR256154R3105	DMA63NpB10/300	460	0,126
2CSR256154R3135	DMA63NpB13/300	448	0,162
2CSR256154R3165	DMA63NpB16/300	448	0,225
2CSR256154R3205	DMA63NpB20/300	448	0,266
2CSR256154R3255	DMA63NpB25/300	471	0,232
2CSR256154R3325	DMA63NpB32/300	471	0,340
2CSR256154R3104	DMA63NpC10/300	460	0,126
2CSR256154R3134	DMA63NpC13/300	448	0,162
2CSR256154R3164	DMA63NpC16/300	448	0,225
2CSR256154R3204	DMA63NpC20/300	448	0,266
2CSR256154R3254	DMA63NpC25/300	471	0,232
2CSR256154R3324	DMA63NpC32/300	471	0,340

Glossary

Environmental impact Indicators	
GWP-total	Global Warming Potential total (Climate change)
GWP-fossil	Global Warming Potential fossil
GWP-biogenic	Global Warming Potential biogenic
GWP-luluc	Global Warming Potential land use and land use change
ODP	Depletion potential of the stratospheric ozone layer
AP	Acidification potential
EP-freshwater	Eutrophication potential - freshwater compartment
EP-marine	Eutrophication potential - fraction of nutrients reachin marine end compartment
EP-terrestrial	Eutrophication potential - Accumulated Exceedance
POPCD	Formation potential of tropospheric ozone
ADP-m&m	Abiotic Depletion for non-fossil resources potential
ADP-fossil	Abiotic Depletion for fossil resources potential, WDP
WDP	Water deprivation potential

Resource indicators	
PENRE	Use of non-renewable primary energy excluding renewable primary energy resources used as raw
PENRM	Use of non-renewable primary energy resources used as raw material
PENRT	Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials
PERE	Use of renewable primary energy excluding non-renewable primary energy resources used as raw material.
PERM	Use of renewable primary energy resources used as raw material
PERT	Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)

Secondary materials, water and energy resources		Waste category indicators	
SM	Use of secondary materials	HWD	Hazardous waste disposed
RSF	Use of renewable secondary fuels	N-HWD	Non-hazardous waste disposed
NRSF	Use of non-renewable secondary fuels	RWD	Radioactive waste disposed
FW	Net use of fresh water		

Output flow indicators		Optional indicators	
CfRu	Components for re-use	Tot PE	Total use of primary energy during the life cycle
MfR	Materials for recycling		
MfER	Materials for energy recovery	Efp	Emissions of Fine particles
EE	Exported Energy	IrHH	Ionizing radiation, human health
		ETX FW	Ecotoxicity, freshwater
		HTX CE	Human toxicity, carcinogenic effects
		HTX N-CE	Human toxicity, non-carcinogenic
		IrLS	Impact related to Land use / soil quality

References

-
- [1] PEP ecopassport® PROGRAM. PCR-ed4-EN-2021 09 06. Product Category Rules for Electrical. Electronic and HVAC-R Products.
- [2] PEP ecopassport® PROGRAM. PSR-0005-ed3-EN-2023 06 06. Specific rules for Electrical switchgear and control gear Solutions.
- [3] PRé Consultants. Software SimaPro v 9.5. 2024 (www.simapro.com).
- [4] ISO 14040:2006/Amd 1:2020. Life cycle assessment. Environmental management. Principles and Framework. International Organization for Standardization. 2020.
- [5] ISO 14044:2006/Amd 1:2017/Amd 2:2020. Life cycle assessment. Environmental management. Requirements and guidelines. International Organization for Standardization.
- [6] ABB website. <https://global.abb/group/en/about> [accessed 12-01-2023]
- [7] ABB website. <https://global.abb/group/en/sustainability/sustainability-strategy-2030> [accessed 12-01-2023]
- [8] ABB website. (<https://new.abb.com/low-voltage/products/system-pro-m/residual-current-devices/dda200>) [accessed 15-12-2023].
- [9] Ecoinvent. 2022. Swiss Centre for Life Cycle Assessment. v3.9.1 (www.ecoinvent.ch).
- [10] UNI EN 15804:2012+A2:2019: Sustainability of construction works - Environmental
- [11] Google Maps. <https://www.google.it/maps/preview>.
- [12] Sea Rates. <https://www.searates.com/>.
- [13] VAC – Advanced Magnetic Solutions, VITROPERM® 800 / 500 (VITROPERM 500 - 800.pdf
- [14] Wikipedia, Alnico (Alnico - Wikipedia).
- [15] Kruzhanov, Vladislav & Arnhold, Volker. (2012). Energy consumption in powder
- [16] GO CERTIFICATES ABB SPA 2022.
- [17] Eurostat. (https://ec.europa.eu/eurostat/web/products-datasets/-/ENV_WASPAC).
- [18] Eurostat. (https://ec.europa.eu/eurostat/web/products-datasets/-/ENV_WASTRT).
- [19] International Electrotechnical Commission. IEC/TR 62635 Ed. 1.0 en:2012. Guidelines For
- [20] Product Environmental Footprint (PEF), Annex_C_V2.1_May2020.
- [21] Imballaggi & Riciclo. 2011. Packaging in legno dalla culla alla culla.
- [22] PlasticFinder (<https://www.plasticfinder.it/>) [accessed 06-03-2024].
- [23] Delem, L. and Wastiels, L., 2019, IOP Conf. Ser.: Earth Environ, The practical use of module
- [24] EEA (European Environment Agency), Technical report No 3/2012. Annual European
- [25] EN 50693:2019. Product category rules for life cycle assessments of electronic and
- [26] Ecoinvent. 2021. Documentation for the “Allocation, cut-off, EN15804” system model
- [27] 9AKK108469A4387 PEP ABB-608- LCA AEG DMA 63 N PLUS