

PV-DXF60/24

- For industrial and residential applications
- Wide input range: 100 - 240 - 277 Vac
- Flexible power continuity up to 65 W
- Output: 24 Vdc
- Wide temperature range: -25 to 70 °C
- Overload, overvoltage and short-circuit protection
- DIN Rail IP20
- Extremely small size

Input Data

| | |
|---|--|
| Nominal Input Voltage (2 x Vac) | 100 – 240 – 277 |
| AC Input Voltage range (Vac) | 85 – 305 |
| DC Input Range (Vdc) | 95 – 370 |
| AC Frequency | 45 – 65 Hz ± 5% |
| DC Frequency | 0 Hz |
| Current consumption (Approx..) | 1.2 A (120 Vac) 0.65 A (230 Vac) |
| Inrush Current limitation (Vn and In Load) I ² t | ≤ 25 A ≤ 5 msec. |
| Hold-up Time (Typ.) | > 15 msec (120 Vac) > 30 msec (230 Vac) |
| Internal Fuse (slow – blow, Internal) | 2.5 A |
| External Fuse (recommended) | 10 A curve B |
| External Circuit Breaker (recommended) | 10Acurve B or 6Acurve C |

Output Data

| | |
|---|------------------------|
| Output Voltage isolated DC Voltage (Vn) | 24 Vdc ± 3% |
| Adjustment range (Vadj) | 22.5 – 28 Vdc |
| Start up with Strong Load (capacitive load) | ≤ 30.000µF |
| Turn-On delay after applying mains voltage | 1 sec. (max) |
| Continuous Current -25 - +55°C In | 2.5 A |
| Continuous Current +55 - +70°C In | Derating 2%/K |
| Power Boost Current at 24 Vdc 55° C In | 3 A ≤ 3 min. |
| Max Short Circuit current (Icc) | 3.2 A |
| Enduring Short Circuit current RMS max. | 3.2 A |
| Residual Ripple (with nominal value) | ≤ 100 mV _{ss} |
| Peak | ≤ 150 mV _{ss} |
| Parallel connection to increase power | No |
| Series Connection | Yes (max four device) |
| Redundancy Connection | Yes |

Efficiency

| | |
|---|-------------|
| Efficiency at Vout rated, Iout rated, approx. | 85% |
| Power loss at Vout rated, Iout rated, approx. | 3 W |
| Power loss [W] during no-load operation maximum | 0.3 W |
| Reliability: MTBF at 40°C IEC 61709 | > 980.000 h |

Closed-loop control

| | |
|--|--------|
| Dynamic mains compensation (Vin rated ± 15 %), max. | -0.2 % |
| Dynamic load smoothing (Iout: 10/90/10 %), Uout ± typ. | 2 % |
| Load step setting time 10 to 90%, typ. | 1 ms |
| Load step setting time 90 to 10%, typ. | 1 ms |

Protection and monitoring

| | |
|--------------------------------|---|
| Output over voltage protection | Hiccup. Shut-down output and automatic restart. |
| Short-circuit protection | Hiccup. Shut-down output and automatic restart. |
| Over Load capability | 150% In typ. 200ms |
| Over Voltage Output protection | Yes (typ. 35 Vdc) |
| Status output voltage OK | Green LED |

Environmental Conditions

| | |
|---------------------------------------|---|
| Ambient Temperature operation | -25 up to +70 °C |
| Ambient Temperature Storage | -40 up to +85 °C |
| Humidity at 25 °C in acc. to EN 60721 | 95 % no condensation |
| Vibration (operation) IEC 60068-2-6 | < 15 Hz, amplitude ± 2.5mm < 15Hz-150Hz, 2.3G 90 min. |
| Shock IEC 60068-2-6 | 30g in all directions |

Safety

| | |
|---|--------------------------------------|
| Primary/secondary isolation | Yes |
| Pollution Degree Environment | 2 |
| Insulation voltage (IN/OUT) | 4000 Vac |
| Insulation voltage (Input / Earth, PE) | 2000 Vac |
| Insulation voltage (Out Load & Battery / Earth, PE) | 500 Vac |
| Galvanic isolation to: EN 62368 and EN 50178 | Safety extra-low output voltage Uout |
| Degree of protection (EN 60529) | IP20 |

Mechanics Data

| | |
|-----------------------------------|---------------------------------------|
| Screw type connection | 0.6 - 0.8 Nm |
| Connections Supply Input: L, N: 1 | 0.2 - 2.5 mm ² (24–12 AWG) |
| Connections Output: +, - | 0.2 - 2.5 mm ² (24–12 AWG) |
| Protection class | II |
| MTBFat 40°C | > 4.300.000 h |
| Housing material | Polycarbonate |
| Dimension (WxHxD) DIN 43880 | 54 x 90 x 55 mm |
| Weight (approx.) | 0.2 Kg |

Regulatory Compliance

- CE mark in conformity with EU Directives: EMC, LVD and RoHS.
- UKCA mark in conformity with UK S.I. 2016/1091, 2016/1101, 2012/3032.
- REACH Regulation 1907/2006.

Approvals (Pending)

- UL 61010-2-201 Safety requirements for electrical equipment for measurement, control and laboratory use.
- UL 1310 NEC class 2 Limited Power Source.

EMC

- EMC Immunity EN 61000-6-2 for industrial environments: EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11.
- EMC Emission EN 61000-6-4 for industrial environments (Class A).