



Warning! Hazardous voltage!

Installation by person with electrotechnical expertise only.



Warnung! Gefährliche Spannung!

Installation nur durch elektrotechnische Fachkraft.



Avvertenza! Tensione pericolosa!

Fare installare solo da un elettricista specializzato.

Avertissement! Tension électrique dangereuse!

Installation uniquement par des personnes qualifiées en électricité.

¡Advertencia! ¡Tensión peligrosa!

La instalación deberá ser realizada únicamente por electricistas especializados.

	LS55N-30 LS75N-30		M 8 8 Nm 71 lb.in			1 x 10...95 2 x 6...35 AWG 6...2/0	1 x 10...70 2 x 6...35	1 x 10...70 2 x 6...35	1 x 10...70 2 x 6...35	L = 20 mm 0.79 in	-	14 mm x 14 mm 0.55 in x 0.55 in	-	-
	LS90N-30 LS110N-30	-	M 8 18 Nm 160 lb.in	-	-	-	-	-	-	-	-	ATK185	24 mm 0.94 in	W=22 mm 0.87 in T=8 mm 0.31 in
	LS132N-30 LS160N-30 LS200N-30		M 10 28 Nm 248 lb.in									ATK300 ATK300/2	32 mm 1.26 in	W=32 mm 1.26 in T=10 mm 0.39 in
	LS55N-40 LS75N-40		M 8 8 Nm 71 lb.in			Stranded 1 x 10...95 2 x 10...95 AWG 6...4/0 AWG 6...4/0	1 x 10...70 2 x 10...70	-	-	L = 20 mm 0.78 in	-	-	-	-
	LS55N-40 LS75N-40 +CSK75N4		M 6 9 Nm 80 lb.in									-	22 mm 0.86 in	W=20 mm 0.78 in T=5.5 mm 0.22 in
	LS90N-40 LS110N-40	-	M 8 18 Nm 160 lb.in	-	-							ATK185	24 mm 0.94 in	W=24 mm 0.94 in T=8 mm 0.31 in
	LS132N-40 LS160N-40 LS200N-40		M 10 28 Nm 248 lb.in									ATK300 ATK300/2	32 mm 1.26 in	W=32 mm 1.26 in T=10 mm 0.39 in
	LS280N-40 LS375N-40		M 10 18 Nm 160 lb.in									-	55 mm 2.17 in	-

	LS55N LS75N	M 3.5 1 Nm 9 lb.in	-	Ø 5.5 mm 0.22 in	Pz 2	mm^2	mm^2	mm^2	mm^2													
	LS90N LS110N																					
	LS132N LS160N LS200N																					
	LS280N LS375N	M 3.5 1 Nm				mm^2	mm^2	mm^2	mm^2													
	H06N-L-11 H06N-L-11B H07N-L-11 H07N-L-11B	M 3.5 1 Nm 9 lb. in				mm^2	mm^2	mm^2	mm^2													
	VB75NE																					
	H06N-F-01 H06N-F-10																					